

Chemicals Company Delaware Valley Works Marcus Hook, Pennsylvania 19061 Phone: Chester, Pa (215) 485-1857 R. Sobel

A. L. Schwartz

L. A. Mattioli

J. B. Oliver

August 15, 1980

Mr. Kenneth R. Weiss, Resource Engineer Solid Waste Management Branch -Division of Environmental Control-DNRECT Tatnall Building Dover, DE 19901

Dear Mr. Weiss:

At a meeting on June 24 with our Regional Environmental Supervisor, David T. Murphy, you discussed the presence of "red mud" (residual iron oxide from pyrites ore burning) contained within our gypsum impoundment area. As a result of the meeting we were requested to submit our assessment of the situation and a proposal which satisfactorily protected the area from contaminated run-off.

Although you already have much of this information which was discussed during your previous meeting it is important to highlight again. The sketch showing locations of the core samples together with the boring logs indicate the presence of "red muds" (Exhibit No. 1). Specific reference is to Boring No. 2 on the sketch and Boring No. TB-2 of Walton's Boring Log, samples 4 and 5 (Page-5).

The analytical data shows that although the total concentration of various metal impurities are relatively high the leachate analyses are very low (Exhibit No. 2). Specific reference is to Lancaster Laboratories' Table I where Boring No. 2, samples 4 and 5 have been made into LLI's Composite Sample No. G-2307 (Page-3). Specific references are to Lancaster Laboratories' Tables II and III analytical results on Sample No. G-2307 (Pages 4 and 5). Further corroboration is shown by analytical data on in-plant leachate tests run at pH's of 4, 7 and 10 (Exhibit No. 3). An in-plant report on results from leachate tests performed on the filter cake residue from the South Plant Waste Treatment system are also included since this is the only material currently being retained on site (Exhibit No. 4).

The "red Mud" is iron oxide formed when pyrites ore (iron sulfide) was burned at 1800° - 2000° F. Observations through a microscope have shown the particles to be glassy in appearance, fused with no apparent porosity. This could explain the low levels of metals in leachate extractions. Based on the location of the "red mud" in respect to the volume of gypsum we feel that in addition

to the "red muds'" insolubility its encapsulation in the gypsum renders it inaccessible. As indicated in the boring log, Exhibit No. 1: Page-5, Samples No. 2, No. 3 and No. 3A, layers of some gypsum were so hard a diamond core had to be used.

Using 3 metals as indicators, (copper, lead, zinc), analyses of our Main Outfall (001) and intake water from the Delaware River (samples taken concurrently) show no evidence of contamination from the containment area. The values obtained are within NPDES permit limits. The gypsum containment is bounded on one side by our Main Outfall (001) and on another side by Middle Creek both of which flow into the Delaware River which forms the boundary on a third side. Monthly analyses for the last 5 years are attached (Exhibit No. 5).

----Summary ---

Based on the accumulated information we feel the "red mud" should remain in place. Even though the containment area lies within the 100 year flood plain boundary the insolubility of the fused material would render it as harmless as normal soil erosion products. The fact that leachate tests show the material passes non-hazardous waste criteria eliminates the need for monitoring wells. Our proposal is to expend our efforts in contouring the site and providing vegetation for erosion prevention. The program for achieving this is attached.

If further information is needed contact Mr. J. B. Oliver, Environmental Supervisor; telephone 798-0621, Extension 319.

Very truly yours,

P. A. Brucknerk

P. L. Brueckner Plant Manager Delaware Valley Works

PLB/ld Attachments

Cc: Mr. Robert L. Allen-Chief, Hazardous Materials Branch
USEPA, Region III 3AH30
6th and Walnut Streets
Philadelphia, Pa. 19106

Mr. Wayne Naylor Environmental Scientist Hazardous Materials Branch USEPA, Region III 3AH30 6th and Walnut Streets Philadelphia, Pa. 19106

Background and General Discussion

The proposed area to be reclaimed is located on property owned by Allied Chemical Corporation as a portion of the Delaware Valley Works-South Plant. The site is bounded on the south by the Delaware River, on the east by Middle Creek, on the West by the Delaware Valley Works' main Outfall (001, NPDES Permit #0000655. The north side of the site borders the area of the former hydrofluoric acid plant.

The object of the reclamation and revegetation project is to further seal the site from potential rain water percolation and to establish a vegetation cover to minimize erosion and fugitive dust.

The site consists of five (f) distinct sections each requiring separate methods of site preparation to insure adequate slope preparation. These sections have been given the following designations:

- 1 Top: Any area with a slope of less than 1 cm 3
- 2 North Slope: The area on the opposite side of the river
- 3 East Slope: The area fronting on Middle Creek
- 4 West Slope: The area fronting on the plant discharge stream
- 5 South Slope: The area fronting the Delaware River

Each of these sections will be discussed separately including the proposed plan of action to achieve a successful reclamation.

The material to be used will consist primarily of the non-hazardous filter cake generated at the location's South Plant Waste Treatment System. The leachate analysis of this material is presented in Exhibit No. 4. This material will be moved to the site and used to establish the final site slopes. Based on a test plant and the fugitive growth which has established itself the material appears able to support and propogate vegetation.

Reclamation

Each section will be developed in a systematic order with the higher priority slopes reclaimed first to minimize future erosion and dusting problems and to improve the aesthetic value of the site

West Slope

This area parallels the plant discharge and is the area with the most critical slope ratio. The proposed slope to be established in this area will be no more than one on one with every effort made to obtain a one on three slope. The problem is the lack of room to establish a leasser than one on one slope because of the height of the site and the close proximity of the plant effluent stream. Once a portion of the slope is established it will be stabilized with jute, cotton or paper netting and then mulched and seeded according to the revegetation plan. A twelve foot wide road way will be maintained between the toe of the slope and the stream.

South Slope

The base of the present slope will be the toe of the new slope which will rise on a one on three grade to the top of the site. There should not be any need to artificially stabilize the slope in this area. A twelve foot wide roadway will be maintained between the toe of the slope and the graded approach to the river front rip rap bulk head.

North Slope

The slope in this section is greater than one on three but the location has been successful in establishing vegetation. The plan is to finish grading as quickly as possible and to begin revegetation. Artifical stabilization will be utilized only in segments appearing to present erosion problems.

Top

The entire top of the site will be graded to slopes of not more than one on ten nor less than one on twenty with the high points along the south and east slopes. This will cause excessive rainwater run-off to be diverted from direct drainage to the plant effluent stream and the river.

East Slope

This is the final section to be reclaimed since it will require the most fill to obtain the desired one on three slope. It will be in this area where a twelve foot wide service road will be maintained to provide access for maintenance to the top of the site. The final slope will be one on three using the edge of the top for a reference point.

Revegetation

The initial and major effort for the revegetation is to establish a perennial, maintenance free, natural cover using plants with nitrogen fixing properties. To accomplish this all sections will be hydroseeded at the following rate:

Creeping Red Fescue - Commercial Seed - 6 pounds per acre

Crown Vetch - Commercial Seed - 30 pounds per acre

Rye Grass - Commercial Seed - 100 pounds per acre


Fertilizer - 12-24-12 - 600 pounds per acre


Mulching - Hay or Straw - 2 tons per acre

The seeding dates will be in the spring (April-May) and fall (September-October).

The West Slope and North Slope sections will have a soil sealer-stabilizer applied at the rate of 45 gallons per acre.

Modifications will be made to the seeding mixture if unexpected difficulties are encountered.





CORE SAMPLING of SOLID WALTE MOUNTAIN DELAWARE WORKS.

- DRILLING BY WALTON CORP
- ANALYSES BY LANCASTER LARGRATER REPORT DATED DEC 3 1974.

57-58 58-59 59-60

							Ex	subit of	vil: rage.	
\mathcal{L}	,					WALTON CORPOR Drilling Contractor P. O. BOX 1097, NEWARK, DEL. BORING LOG	7		BLOWS ON CASING B 0- 1 1- 2	
)	NAME	Allie	ed Che	emical			PROJECT NO.		2- 3 3- 4 4- 5	
						••••••••••			5- 6	
	BORIN					RILLER	15 15 15 15 15 15 15 15 15 15 15 15 15 1		7- 8	
	WEATH	T	B -1		101	B. Erickson RFACE ELEVATION	DATE 10-7-7	4	8- 9 9-10	
	WEATH	Clear	·		50	RFACE ELEVATION	DATUM		10-11	
		Sample			Strata			*Blows	11-12	
	Sample No.	From	- Feet	From	To	Driller's Description	of Materials	A	13-14	
	No.	From		1	10			 	14-15	
		ļ	ļ	0	1.0	Dry Gray Fill (Med.	Hard)		16-17	
		<u> </u>	ļ	1.0	2.0	Wet Soft layer Gray	Fill	<u> </u>		
	1	4.0	5.5	3.0	5.5	Lt. & Dk. Gray Fill	Gray Fill (Wet) Med. Ha		18-19	
	2	9.0	10.5	1			" " (Dry)			
		1		1	7.5	Soft Wet Layer	t Layer			
			1	1 .	i	ľ			22-23	
	<u> </u>	 		1	!	Hard Dry Layer	(11 1)		24-25	
	` <u> </u>	 	 		1	Lt. Gray Very Soft Fi	11_(Wet)	 	25-26	
).				12.0	12.5	Hard Dry Dark Gray			26-27	
)	· <u></u>			12.5	13.0	Soft Wet Dark Gray			27-28	
-	3	14.0	15.5			Lt. Dk. Gray Fill (Ha	rd) Dry		29-30	
	4	19.0				Same			30-31	
		24.0				Same (See remarks)			31-32	
	_5	24.0	25.5	-					33-34	
					27.0	Refusal on Augers		- - -	34-35	
ļ									35-36 36-37	
									37-38	
		^							38-39	
									39-40 40-41	
ı									41-42	
t									42-43	
-				+					44-45	
- }									45-46	
-									47-48	
L	1	<u>_</u> <u>_</u>							48-49	
	4 N	ar of bloc	ws of 140) lb bam	mar droi	oped 30 in. required to drive 2 in. s	nllt on ee - eeles f	an analy of Alexander	49-50	
	. in. incr		W2 01 140) ID. ILam	mer mol	ped 30 m. required to drive 2 m. s	put-spoon sampler 1	or each of thre	51-52	
						pped 18 in. required to drive			52-53	
١.	•					18"(.topto.bottom.o			53-54 54-58	
)	loos	en.mat	erial	. S	poon.	Sample.very.wet.w/har	d.core		55-56	
	• •	le war					GROUND WAT		56-57 57-58	
				• • • • • • • • • •	• • • • • • •		1	ı	1-00	

55-56 56-57

57-58 58-53 55-60

GROUND WATER

•					•		app	uo	•	,	, age -
		7			WALTON CORPO Drilling Contract P. O. BOX 1097, NEWARK, DE	tor	-				BLOWS OF
•	\\ \	₹,					1//11				0- 1
.)	4	3			BORING LO	G					1- 2
·. •	I				~.						3- 4
Ar A 3.671	 ^ 7 7 4	ođ ሮክ	emica:	1		To a	. TD C				4-5
NAME					• • • • • • • • • • • • • • • • • • • •			• • • • •	• • • • •	••••	5- 6
	Clay	mont.	Dela	ware	• • • • • • • • • • • • • • • • • • • •	sui	PERVISOR	.			6- 7
	'										7- 8
BORIN	G NO.	TB-1	A	Di	C. Nau	DATE	10-1	- 5_ワ	 h		8- 9
WEATH				įsu	RFACE ELEVATION	DATU	M 10-1	<u>) </u>	~		9-10
Coc	ol. C	Loudy									10-11
		ample		h Strata				1	•B	lows	12-13
Sample		ı - Feet		Peet	Driller's Descript	ion of Ma	terials			A	13-14
No.	From	To	From	1 To							14-15
1	40	5.5			Gray Fill	Hard	Chips		T		15-16
			<u> </u>		n H		"		+	+	16-17
2	19.0	10.5	1				·				17-18
3	14.0	115.5	<u> </u>		te 11 -	· n	11				19-20
,	1								1		20-21
		1			0.55+ 4.03		·		1	1	21-22
	 	+	 	 	Offset 18*				-		22-23
	ļ <u> </u>			<u> </u>	W.I. 6.0°				↓		23-24
	1	1	1								24-25
					TB 1C				1		25-26 26-27
	1. 0	1			I .	77 7 /	01		 	+	27-28
<u> </u>	4.0	5.5	0	ļ	Gray Fill s/Damp	_ Hard	unips		ļ	-	28-29
2	9.0	10.5			Gray Fill	***	*		<u> </u>		29-30
3	14.0	15.5		17.5	Gray Fill	4					30-31 .
	- :	1-2-2							 	1-	31-32
			17.5		Very Wet	 			 	╀	32-33
4	19.0	20.5			Gray Fill v/Wet	Hard (Chips		<u> </u>	<u> </u>	33-34
	•				W.L. 10-16-74 5.0						35-36
5	2/1 0	25.5			Gray Fill (v. wet)	Hard (hing				36-37
					· · · · · · · · · · · · · · · · · · ·			-		-	37-38
6	29.0	30.5			Gray Fill " "	Soft C	hips			 	38-39 39-40
7	34.0	35.5			Gray Fill " "	Hard C	hips				40-41
8 -	.39 . n	40.5	<u> </u>	1	Gray Fill w/Native N	Materia	ا ر		_		41-42
	,,,,,			- 1	•			\neg			42-43
٠.					W.L. 25.3 @ comple	tion_					44-45
	•										45-46
			·						_		46-47
									-		47-48
						-					49-50
		ws of 140	0 lb. ham	mer dro	pped 30 in. required to drive 2 in	. split-spoo	n sampler fo	or eac	ch of	three	50-51
in incr	ements.						_			1	51-52
3 Numb	er of blo	ws of 30	0 lb. han	ımer d roj	pped 18 in. required to drive	in. casii	ng 12 inches.	•		I	52-53 53-54
EMARK:	S:		• • • • • • • • •	•••••		•••••	• • • • • • • • • • • • • • • • • • • •	• • • • •			54-55

BLOWS ON CASING B

0- 1

1- 2

•	
---	--

WALTON CORPORATION

Drilling Contractor P. O. BOX 1097, NEWARK, DELAWARE 19711

BORING LOG

3- 4 NAME Allied Chemical PROJECT NO. ... 4- 5 5- 6 Claymont, Del. Supervisor 6- 7 7- 8 8- 9

BORING NO. DRILLER DATE S. Bethard Surface ELEVATION 10-4-74 TB-29-10 WEATHER 10-11 Clear 11-12

Ī	Sample	mple Bample Depth Strata Depth - Feet Feet No. From To From To			ľ			lows	11-12	
. [-					Driller's Description of Materials	1		A	13-14
L	<u> </u>	Fion	10	FIUL	10					14-15
Γ			-	0	3.0	Material Dry outside of augers	1		T	15-16
H		 	1		1-11-4		1	\top	1	16-17
\perp			-		· ·	LtGray color-	┼-		1	
L				3.0	L	Material wet outside of augers				18-19
Г						Dk. Gray				20-21
\vdash		1. 0	-		1		1	+-	 	21-22
\perp	1	4.0	5.5		5.5	Variegated Fill Sample Dry	-		 	22-23
			<u> </u>		<u> </u>	Outside of Spoon Wet		<u>.</u>	1	23-24
Γ	2	9.0	10.5	55		Gray & Dk. Gray Layered Fill				24-25
•	~	7.0	120.	1.	 		1-	+-	1	25-26
-			<u> </u>	<u> </u>		Layers of Wet & Dry Material in	<u> </u>		ـــــ	26-27
						Spoon	ŀ	l		27-28
Г		41. 0	41	1			-	1	1.7	28-29
\vdash	3_	14.0	14.5		 -	Lt. & Dk. Gray Fill Very Hard		╂	-	30-31
-	• •					Dry Refusal on Spoon @ 14.5				31-32
	3A	14.5	15.5			Same See Remarks (Dry)				32-33
\vdash	$\overline{}$				00.0			1 :	-	33-34
\vdash	4	19.0	20.5		20.0	Variegated Fill (Red, Brn., Gray) T	pp S	oft	34-35
				20.0	21.0	White & Yellow Fill Soft Botto	m (1	Vet)		35-36
Г	5	24.0	25 5			_				36-37
	3-1	4.U	62.2	الاملع		Lt. & Dk. Gray Fill w/Layers				37-38
_						Variegated Fill (Red Gray Brn.)	Da	np		38-39
	6	29.0	30.5		30.0	Gray Silty Clay w/Tr. Mica	Dar	np		40-41
Г	$\neg \neg$					Gray Silty Clay w/Tr. Vegetation				41-42
	<i>L</i>	J .T. V.		- 1		GLAY DILLY CLAY WITT TERE LACTOR				42-43
<u>L</u>				34.0	35.5					43-44
	· 1.		1		i				1	44-45
_							-			45-46 46-47
										47-48
								-	1.	48-49
						<u> </u>			=	49-50

A Number of blows of 140 lb. hammer dropped 30 in. required to drive 2 in. split-spoon sampler for each of three a in increments.

1 Number of blows of 300 lb. hammer dropped 18 in. required to drive in. casing 12 inches. EMARKS: S = Spoon D.C = Diamond Core

Sample #2 Alternating Hard & Soft Layers Under 1.0" encountered

when driving spoon

...3A .- Cored. w/NX. Hamond. Core.....

GROUND WATER

51-52 52-53 53-54

50-51

54-55

55-56 56-57

57-58 58-59 58-60

LANCASTER LABORATORIES, INC.



2425 NEW HOLLAND PIKE LANCASTER, PENN. 17 Telephone (717) 656-2301

"The Reliable Hands of Lancaster"

December 3, 1974

Mr. K. F. Borden, Project Manager Box 2105 R Corporate Engineering Dept. Allied Chemical Corp. Morristown, NJ 07960

Dear Mr. Borden:

Enclosed with this letter report are three tables compiling all of the trace metal analytical results performed in duplicate for the 10 composite samples of industrial by-product waste as stipulated in your purchase order #773108615.——In order to discuss these results in a meaningful manner it is necessary to provide background information on these samples regarding the drilling location, the sample compositing methods, and the problems encountered in total digestion procedures.

A total of 32 samples were sent to us. These represented samples taken approximately every 5 feet in depth for a complete drilling at level 2, two drillings at level 3, and two additional incomplete drillings at level 3. Reference is made to our original proposal for the numbers designating the three levels of the waste pile. Since analyses on 10 composite samples were requested, 20 drilling samples were selected for drying and grinding. Table I summarizes the composited samples, listing both the levels from which they were taken, the depth at which they were taken, and Lancaster Laboratories sample numbers for the composites of every two five foot drillings. After these drilling samples were composited, 100 g quantitatives were taken in duplicate for analysis of all the metals, and the duplicate samples are distinguished by an (a) and (b) following our sample numbers (see Table II).

As indicated in past correspondence our digestion procedure for determining total concentrations of each of the elements consisted of an aqua regia digestion. For all past samples of the HF by-product residue this digestion procedure proved adequate for 100% dissolution; however, in this series of samples only 2 were completely solubilized by treatment with hydrochloric and nitric acids. These were G-2303 and G-2309. Sample G-2310 was almost completely solubilized. We did not attempt to get complete solubilization by other digestion methods such as strong alkali fusion for a number of reasons; a. alkali fusion would not be applicable for all the elements and certainly-losses of some would be incurred; b. the aqua regia digestion procedure has worked well for the HF residue in the past and to change at this point would not allow valid comparisons to be made with our past results; c. if concentrated HCl and concentrated HNO, in combination cannot render such a sample soluble, it is difficult to conceive how such a material could cause harm to the environment through natural leaching processes. Thus all of the samples were treated with agua regia as in the past, and any insoluble residue was filtered prior to analysis.



Exhibit No. 2: Page -

TABLE II

Elemental Composition of Drilling Samples*

		LLI	•			-· ·			• •	. •	·	
Level	<u>Depth</u>	Sample No.	Cu	·Cr	Pb	Cd	Be	Zn	· Ni	. <u>Hg</u>	Ās	<u>∵</u> ₹
3:	14.0 - 20.5	G-2303A	7.5	9.4	85.6	<0. 3	51 (0.31	. 26.2	<3.1	3.0	0.20	וַ (
	• • •	: G- 2303B	9.4	10.0	89.3	3 (0. 3	51 < 0.31	. 26.3	<3.1	3.4	0.26	;
		•							٠			
. 3	34.0 - 40.5	G-2304A		_			<0.31		٠.	·	.63	
:		G- 2304B	101	20.0	428	2.5	<0.31	200	<3.1	<0.31	6?	Ž
			-0.0		-(-		1 (0.31	22.5	.7.7			· ,
2 .	4.0 - 10.5	-										
•••	-	G-2305B	11.9		15.6	₹0.3	1 <0.31	22.5	43.1	<0.31	1.9	
2	-14.0 - 20.5	G-2306A	 102	12-5	212	1.6	(0,31	236	· <3-1	 (0.31	45 -	- •
· ·	1100 - 2007	G-2306B				•	<0.31			•	40	
•	• • • • • • • • • • • • • • • • • • • •	.u-2,55B	٠.	10,0	±/+		-		1,5-1	10.01	•••	
2	24.0 - 30.5	G-2307A	363	56.1	5550	10.9	<0.31	1880	13.7	93	410	ϵ
٠.	. • • • • • • • • • • • • • • • • • • •	G-2307B	429	51.6	. 5810	9.5	₹0.31	1830	15.5	5 9 9	540	· -
•	· .	•						. •		· .		
2 .	34.0 - 35.5	G-2308	17.4	37-3	71.6	<0.31	<0. 31	112	16.8	1.1	63	. 2
		G- 2308	17.4	34.7	77-9	<0.3 1	<0.31	101	20.5	0.93	53]	. 3
					·							-
3 .	4.0 - 10.5		•		•		(0.31		-	14		: []]
. ••		G-2309B	8.1	10.0	16.2	1.1	<0.31	56.1	<3.1	15	4.4	
7	-14.0 - 20.5	G-2310A	6.0	6-	73.77	٠., · د ۲۵ عا	₹0.31	25.0	/Z 7	6.0	10-	·:
<i>)</i>	14.0 - 20.5	G-2310B	-				<0.31			•	•	
		G-2510B	0.1	10.0	11.9	10-51	(0.51	-27•1	· • • • • • • • • • • • • • • • • • • •	J•5 ;	0.0	
 3	24.0 - 30.5	G-2311A	8.1	18.7	62.5	50.31	<0.31	13.7	< 3.1	2.2	0.20	2
		G-2311b			_	. •	<0.31	-		2.1	0.17	· 5
			•		: .						·	•
3	34.0 - 40.5	G-2312A	103 - 2	26.1	1270	1.9	<0.31	106	(3-1 -	0.31	27	Ļ
	. : : : :	G-2512B	122	18	1420 [2.2	<0.31	101 •	<3. 1	0.31	27	=
											-	

^{*}All results expressed in ppm

TABLE III

	Lead	Zinc	Cadmium	Chromium	Copper
G-2304*	1.3	28	0.60	0.50	0.50
G-2307*	4.8	121	<0. 025	0.40	0.20
G-2312*	2.0	13	0.50	0.50	0.75
G-2507 (24.0 - 25.5 ft.)	8480	3120	13.7	49.9	374
G-2307 (29.0 - 30.0 ft.)	5020	1040	5 . 0	78.3	547

^{*}water extract. 30g sample was shaken with 300 ml DD-H_O for 72 hrs. The sample was filtered thru Whatman #41 filter paper and then thru 0.45 micron filter paper. Then 100 ml was acidified and concentrated to 50 ml.

Exhibit me. 1

COMPANY CORRESPONDENCE

TO DIV:

I. C. D.

FROM DIV:

Corporate Engineering

LOCATION:

Delaware Works

LOCATION:

MTC - SOL 3

ATT'N OF:

J. B. Lukas

DATE:

December 27, 1974

SUBJECT:

Delaware Works

Solid Waste "Mountain"

Job No. 10609

The exploratory core drillings in the solid waste mountain at Delaware Works, and the analysis of the core samples, have been completed. The laboratory work is reported in the letter of Lancaster Laboratories, Inc., dated December 3, 1974, which presents analytical data on the mountain material on the same basis, and directly comparable with, their earlier report on the HF residue which was prepared for Delaware Contracting Company as the base for the usage approval granted by the Delaware Department of Natural Resources.

Since the composition of the mountain differs, and there are zones of high concentrations, it is believed that a review of these December 3 findings and a discussion of their significance and completeness is important before proceeding with plans to offer this material for sale. Lancaster Laboratories' Dr. Hess is available to attend if we so request.

It is the writers suggestion that we schedule such a meeting at Delaware Works at our early opportunity, in which we can evaluate this data and program our next moves; we will be pleased to make the arrangements if you concur.

For your prior information, we enclose a copy of the subject Report and a sketch showing the locations from which the core samples were taken.

K. F. Borden Project Manager

KFB: cjt: 5/1

enclosure

cc: J. M. Quinn - Morristown Office

AF Jahr

DELAWARE WORKS DEC 30 1974 DO NOT HOLD ton Circled person to tite to treture to Main Office to the										
EGN RWH KWB BC LGE JH	FJD GEK LFS TCJ 6WS EJC EJC SEB	CPS CWM CDH WDS WJA DCB WEP HHT								
FXM BWC JBP	RCF JWB √EAG	SJF MC								

Analytical Data (mg/l)
Main Outfall (001) and Delaware River Water Intake

)		Copp	er_	Le	ad	Zino	<u> </u>
Mon	th	Outfall	Inlet	Outfall	Inlet	Outfall	Inlet
1978 Jan		.019	.017	.03	.02	.09	.11
	ruary	.02	.02	.025	.03	10	.12
Mar		.05	.02	.07	.02	.19	.11
Apr		.02	.016	.02	.014	.04	.066
May		.02	.02	.01	.01	.04	.07
Jun		.02	.01	.02	.01	.05	.04
Jul	•	.02	.02	.02	.02	.08	.07
Aug		.02	.029	.02	.037	.05	.14
	tember	.04	.01	.04	.01	.15	.05
	ober	.01	.01	.01	.01	.08	.06
	ember	.02	.01	.04	.02	.07	.06
Dece	ember	.02	.01 -	.03	.02	.09	.07
1979 Janı	ıarv	.02	.02	.03	.03	.10	.09
	ruary	.03	.02	.02	.01	.10	.07
Marc	-	.04	.01	.04	.01	.12	.05
Apri		.03	.01	.03	.01	.11	.04
May		.02	.01	.02	.01	.05	.04
June	<u>:</u>	.03	.01	.03	.02	.09	.07
July		.02	.01	.02	.01	.06	.04
Augu		.013	01	.02	03	.027	.028
	ember	04	.02	.05	.01	.045	.12
Octo	ber	.03	.02	.02	.02	.05	.03
Nove	mber	.01	.04	.01	.06	. 08	.04
Dece	mber	.01	.02	.02	.01	.04	.04
					0.1	0.7	0.65
1980 Janu		.02	.02	.02	.01	.07	065
Febr		.018	.012	.062	.023	.066	.075
Marci		.023	.033	.063	.059	.012	.12
Apri	T	.024	.013	.07	.068	-18	.16
May		.03	.019	.08	.24	.13	.16
June		.018	.012 .017	034	.03	.045	.053
July		.021	. 017	.045	.036	.077	.068
Augus							
septe	ember						

September
October
November

December

TABLE I

Level	Boring Number	Walton's Sample No.	Depth(ft.)	LLI's Composite Sample No.
5	2 2	1 2	4.0 - 5.5 9.0 - 10.5	G-2305
	2 2	3° 3A	14.0 - 14.5 14.5 - 15.5	G-2306
	2 2	. 4 5	19.0 - 20.5 24.0 - 25.5	G-2307
•	2 2	6 7	29.0 - 30.5 34.0 - 35.5	G-2308
. 3	1B 1B	1 2	4.0 - 5.5 9.0 - 10.5	G-2309
	18 18		14.0 - 15.5 19.0 - 20.5	G-2310
•	1B 1B	5 6	24.0 - 25.5 29.0 - 30.5	G-2311
•	1C 1C	7 8	34.0 - 35.5 39.0 - 40.5	G-2312
3 .	3 3	3 4	14.0 - 15.5 19.0 - 20.5	G-2303
	3	8	34.0 - 35.5 - 39.0 - 40.5	G-2304

- divid inedow as is in - At, We (land ×x 81.0 9/5 10> 1.67 1 '0>. 8,200 6.0 per ~00 t 10 988 195 988.0 15,6> 10'0> 90'0 50,8 90,0 10'0> 1005 Q'Q' 8'5 / 1'0> 059 N 70'0 10'0> 5 50.0 20,0 0°03 0'09) 5810 105 1'0> 9 0 50,0 X0'2 9110 ۵, کې 02,0 22,0 10.02 mgg 10.07 10'0 $\mathcal{C}_{\mathcal{U}}$ helichales on

" V V V V V

ATTACHMENT_C

PESTICIDE CONTAMINATED SITES

Initial findings regarding site contamination are contained in correspondence between Allied Chemical and EPA Region III written in 1976 and 1977. To insure no release of Kepone and/or DDT and it's metabolites Allied chemical undertook a large scale paving program in 1978. The paving covers a total of 5.4 acres and is adjacent to eleven buildings. The paving specification encompassed grading excavation, drainage upgrading and surfacing to provide maximum durability. Site excavation material remained on-site and was used for contouring the Northern paved border area.

In light of this corrective measure Allied Chemical accepted as part of its NPDES permit DE 0000655 a "no net increase" parameter on DDT and its metabolites and Kepone dated 6/1/78 and valid through 12/31/82. During this period only 17-of 497 analytical tests (attached) for the contaminants show a numerical value with none exceeding 0.6 ppb. March 1980 through December, 1982 results show no detectable values of the contaminants. The permit was renewed in 1983 and the pesticide monitoring requirement was dropped. No test data is available beyond that time.

OUTFALL #101

PESTICIDE RESIDUAL

CONCENTRATION LISTED IS HIGHEST VALUE FOR THE MONTH.

NOTE:

- A) ALL VALUES IN PPB
- B) LOWER DETECTION LIMIT = 0.2 PPB WITH A STANDARD DEVIATION OF + 0.5 PPB.
- C) N.D. NOT DETECTED.

			•					•
Month	Year	<u>Kepone</u>	op_DDD	op DDE	op DDT	pp_DDD	pp_DDE	pp_DDT
June	1977	40.2			½0.2		ኒ 0 . 2	
July	1977	፟40.1	ሄ0.1	፟40.1	¥0.1	፟ፈ0 . 1	~20.1	₺0.1
Aug.	1977		0.1			፟፟፟40.02		፟፟፟40 。02
Oct.	1977	^ኒ ፈ0 . 1	፟፟፟40.1	40.1	₹0.1	₹0.1	፟40.1	½0.1
Nov.	1977	40 . 1	፟40.1	½0.1	₹0.1	½0.1	40.1	40.1
Dec.	1977	40.1 ا	፟40.1	₹0.1	፟ፈ0.1	፟40.1	₹0.1	₹0.1
Jan.	1978	N.D.	₹0.1	N.D.	N.D.	፟፟40.1	N.D.	N.D.
Feb.	1978		N.D.	N.D.	N.D.	₹0.2	N.D.	N.D.
Mar.	1978	N.D.	N.D.	N.D.	N.D.			N.D.
Apr.	1978	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
May	1978	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
June	1978	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
July-	1978 -1978	N.D	N.D.	N.D.	·N.D.	N.D.	Ñ.D.	- N-D .
	1978 Rep. as			0.3				
-	small net				-			
	discharge							
Sept	1978	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
	1978	N.D.	N.D.	0.2	N.D.	0.6	N.D.	N.D.
Nov.	1978		N.D.		N.D.		N.D.	N.D.
Dec.	1978	N.D.	ND	N.D.	N.D.	N.D.	N.D.	N.D.
Jan.	1979	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Feb.	1979	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Mar.	1979	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Apr.	1979	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
May	1979	N.D.	N.D.	N.D.	N.D.	0.3	N.D.	N.D.
June	1979 -	N.D	ND	N . D	-N-D	0.3 -	N . D . · ·	N - D - · · ·
Ju l y			SAME					
Aug.	1979	N.D.					N.D.	
Sept	1979	N.D.	N.D.	N.D.	0.5	0.4	N.D.	0.6
Oct.	1979 .	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.

			Vanana	ion DDD	op_DDE	OD DDT	pp_DDD	<u>pp_DDE</u>	pp DDT
Month	Year		<u>кећопе</u>	OP_222	<u>vp</u>				
			N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Nov.	1979		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Dec.	1979		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Jan.	1980		N.D.	N.D.	N.D.	N.D.	0.4.	N.D.	N.D.
Feb.	1980		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Mar.	1980		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Apr.	1980			N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
May	1980		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
June	1980		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Ju ly	1980		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Aug.	1980		N.D.		N.D.	N.D.	N.D.	N.D.	N.D.
Sept	1980		N.D.	N.D. N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Oct.	1980		N.D.	N.D.	N.D.	N.D.		. N.D	N.D.
Nov.	1980		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Dec.	1980		N.D.		N.D.	N.D.	N.D.	N.D.	N.D.
Jan.	1981		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Feb.	1981		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N-D -
Mar.	1981		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Apr.	1981	- ·	N.D.		N.D.	N.D.	N.D.	N.D.	N.D.
May	1981		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
June	1981		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Ju 1 y	1981		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.Ď.
Aug.	1981		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Sept	1981		N.D.	N.D.		N.D.	N.D.	N.D.	N.D.
Oct.	1981		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Nov.	1981		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Dec.	1981		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Jan.	1982		N.D.	N.D.	N.D.	N.D.	. N.D.		- N D -
	1982	a state of the following of		N.D.	т.D.	N.D.	N.D.	N.D.	N.D.
Mar.	1982		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Apr.	1982		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
May	1982		N.D.	N.D.	N.D.		N.D.	N.D.	N.D.
June	1982		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
	1982	• • •		N •D •	. N.D.		N.D.	N.D.	N.D.
Aug.	1981		N.D.	N.D.	N.D.	N.D.	ND.	_	N.D.
Sept	1982		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Oct	1982		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Nov.	1982		N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Dec.	1982		N.D.	N.D.	N.D.	N.D.	N.D.	11	
nec.	1702								

_ ..

ATTACHMENT_D

LINDANE AREA

Attached is data collected in 1976 and 1977 from outfall 101, Naaman's Creek and sediment in the South Works sluiceway (exact location unspecified).

ALLIED CHEMICAL CORPORATION BAKER AND ADAMSON WORKS

BHC ANALYSES

River Water Influent and Storm Water Discharge (Outfall 101)

Sample		Concentrations <u>Lindane</u>	(Parts per bi Other BHC's	llion)
7/26/77	River Water	N.A.	N.A.	
7/26/77	Discharge	0.3	N.A.	
8/22/77	River Water	N.A.	N.A.	
8/22/77	Discharge	0.1	0.5	
8/23/77	River Water	N.A.	N.A.	
8/23/77	Discharge	0.1	0.2	
9/7/77	River Water	4.0.1	0.4	;
9/7/77	Discharge	¼ 0.1	0.7	
9/15/77	River Water	½ 0.1	0.7	
9/15/77	Discharge	½ 0.1	0.7	
10/5/77	River Water	½ 0.1	½ 0.1	
10/5/77	Discharge	¹ 4 0.1	0.5	
10/13/77	River Water	½ 0.1	½ 0.1	
10/13/77	Discharge	½ 0.1	0.2	
11/2/77	River Water	½ 0.1	0.2	
11/2/77	Discharge	0.1	0.6	
11/9/77	River Water	0.1	0.3	
1-1/9/77	Discharge	0.4	1.1	_
12/1/77	River Water	½ 0.1	-½···0 . 1 ····	
12/1/77	Discharge	½ 0.1	0.4	
12/5/77	River Water	½ 0.1	½ 0.1	
12/5/77	Discharge	0.2	0.5	

-N.A. - NOT ANALYZED DUE TO LACK OF SAMPLE---

ALLIED CHEMICAL CORPORATION BAKER AND ADAMSON WORKS

BENZENEHEXACHLORIDE (BHC) ANALYSES

Results in parts per billion (ppb)

Naaman's Creek Samples 10/18/77

	No. I <u>Upstream</u>	No. 2 <u>Upstream</u>	No. 3 Downstream	No. 4 <u>Downstream</u>
Lindane	戈 0.1	0.5	½ 0.1	0.6
Other BHC s	½ ·0·.1 ·	1.0	1.3	1.7

DELAWARE WORKS SOUTH

SAMP LES				•	-	BHC 'S
# 28		Samp. 11/11/ . pt. #1, 0-6		640, 23	m.g.d.	1 PPM
#33		Samp. 11/11/ . pt. #1, 6-1		640, 23	m.g.d.	0.3 PPM
		samp. 11/11/				N.D.
**************************************	Samp	.g.d., .pt. #2, 0-6	· comp •	· · · - ·	The state of the s	
#29	23 m	Samp. 11/11/1.g.d. pt. #2, 6-12	-	m., 64°,		0.3 PPM
#31		Samp. 11/10/7. pt. #3, 0-6		54°, 23 m	.g.d.	0.5 PPM
#26		Samp. 11/10/7. pt. #3, 6-12		64°, 23 m	.g .d .	0.3 PPM
		Samp. 11/10/7				N.D.
		g.d. pt. #4, 0-6"				-
#30	23 m.	Samp. 11/10/7 g.d. pt. #4, 6-12		, 64°,	-	1.0 PPM



COMMONWEALTH OF PENNSYLVANIA DEPARTMENT OF ENVIRONMENTAL RESOURCES

1875 New Hope Street Norristown, Pennsylvania 19401 215-270-1920

December 18, 1985

F. A. Schiffhauer, Plant Manager Allied Corporation Delaware Valley Works - North 6300 Philadelphia Pike Marcus Hook, Pennsylvania 19061

PAD990823742

Dear Mr. Schiffhauer:

We have completed our review on the hazardous waste closure plan submitted on September 11, 1985 which was part of your request to withdraw your hazardous waste Part B application involving the storage of hazardous waste in containers at your facility located in the Borough of Marcus Hook, Delaware County.

This closure plan has been reviewed and has been found to be acceptable. Therefore, I am returning the hazardous waste Part B application to you which means your interim status as a hazardous waste container storage facility is now terminated.

This means you can only function as a hazardous waste generator from this time onward, which means you may only store hazardous waste in containers at your facility for a period of less than 90 days. Once we have inspected your facility to see that the closure has been properly implemented, you will be considered officially closed as a hazardous waste treatment, storage or disposal facility.

If you have any other questions concerning this, you may contact Mr. Larry Lunsk, Regional Solid Waste Facilities Supervisor at 270-1920.

Very truly yours

WAYNE L. LYNN

Regional Solid Waste Manager

cc: Marcus Hook Borough Delaware Co. Planning Dept. Mr. Holmes SW351.1

bc: F. A. Schiffhauer

E. B. Van Orman

A. V. Spivey
E. J. Shields

L. A. Mattioli

H. G. Albrecht .

R. C. Muller

V. A. June

F. H. Hayward

J. A. Leese

F. Cooper ...

E. J. Grezlikowski



COMMONWEALTH OF PENNSYLVANIA DEPARTMENT OF ENVIRONMENTAL RESOURCES

Bethlehem Office 520 East Broad Street Bethlehem, PA 18018 861-2070

January 7, 1986

Re: Closure Plan for Hazardous Waste Management Facility PAD990823742

Mr. F.A. Shiffhauer, Plant Manager Allied Chemical Delaware Valley Works - North Marcus Hook, PA 19061

Dear Mr. Shiffnauer:

The referenced closure plan has been reviewed by our technical staff and found to be acceptable. During the review process the Borough of Marcus Hook responded with the following:

"... that Allied Chemical is not to transport their hazardous waste through downtown Marcus Hook in order to get to I-95 and the Commodore Barry Bridge to Bridgeport, New Jersey. The route they suggest taking is South on Post Road (Rt. 13) to Delaware Route 92 to the Claymont, Delaware interchange of I-95."

An inspection by our field representative on December 31, 1985, confirmed that you are a generator only storing less than 90 days.

Upon completion of actual closure activities, please execute the attached certification and forward them along with the results of any analyses done, to this office.

This completes the Department's requirements for this closure plan. If you have any questions or if I can be of further service, please do not hesitate to call.

James A. Dolan

Solid Waste Specialist

Very truly yours,

JAD/bal

C: L. Lunsk
Field Supervisor

Division of Facilities Management

U.S. EPA Code 3HW33

ate of Inspection 12-31- 8	3.5	Identificat	ion Number	PAD 9	90823
company, Installation Name Alt	lich. C	rf.			
icy delaware	Municip	ality Marc	us H.	ik	
	÷	•		· :	
· Closur Is	LANGE TUD				. 1
: Storige Fa	islite.	in W	isid	1213	t/ }
: # 11 1xx	estilo	az 4,	drem	1) (A	ntai
· Ing Gas		tlipper	1:	i m	il/
Jul ships	and to	c la d	,	il 1	inti
mithin	/ /	month.	Coj	ryflog	1 . 3
manifest !		st) lu	Ul!	u f	erva
	in Spi	med.	is m	s de	/ ,}
			. e*	-	·
· · · · · · · · · · · · · · · · · · ·					<u>; </u>
	<u> </u>				
	·	-			
				· · · · · · · · · · · · · · · · · · ·	
				· · · · · · · · · · · · · · · · · · ·	
	 			·	<u></u>
			• • •	· · · · · · · · · · · · · · · · · · ·	<u> </u>
			· · · · · · · · · · · · · · · · · · ·		 :
· · · · · · · · · · · · · · · · · · ·		· .			
	figarian that				
s inspection report is official notificationmental Resources, Bureau of Solification are showing the inspection are indicated. Viresults of laboratory analyses and theoming, confirming any violations	d Waste Manag wn in this re iolations may review of Dep	ement, inspecte port. Any viol also be discov artment records	d the above ations whic ered upon e . Notifica	installa h were un xamination tion will	ation. acovered on of be
pector (signature) Kales	the all	rult Dat		3//85	
	11/1	5 D-6	e. 12-3		_

ate of Inspection _	12-31-85	<u> </u>	Identification Num	ber PAD9	9082
ompany, Installatio	n Name		orp.		
ity Dela	wore	Municipalit	: Marce	is flow	K'
		·			•
•			•		
•	Jacility	is is	conpli	and.	· · · · · · · · · · · · · · · · · · ·
:	The The	:- has	hun sul	nittell	1 3
•	70 H	Doputm	ent and	will	
	De siene	wed.			
•.			•	•	<u>, </u>
		· - · · · · · · · · · · · · ·			
	• .				:
			· · · · · · · · · · · · · · · · · · ·		
					•
					<u>; ; .</u>
	•	·			· ·
			•	· · · · · · · · · · · · · · · · · · ·	•
•	·			· .	
		· · · · · · · · · · · · · · · · · · ·	· ·	·	
			· · · · · · · · · · · · · · · · · · ·	·	
	·································				
	•				
			-		
ronmental Resources findings of this in ng the inspection a results of laborato	is official notificate, Bureau of Solid Waspection are shown are indicated. Violate and reviant violations indicated indicated.	aste Management in this report. ations may also iew of Departme	, inspected the ab Any violations w be discovered upon	ove installa hich were un n_examinatio	tion. covered
•				7701	
on Interviewed (sig	Lave Ki	· 1/2	Date	7/ ::-	
scror (signature) (· · · · · · · · · · · · · · · · · · ·	1)	Date	-31-85	
: /					•
		-			

Z D H					1- NON-COMPLINCE, Z-COMPLIANCE, 3-NOT APPLICABLE, 4-NOT DETERMINED	
Identification number	C	ST	AT	<u>υς</u>	REQUIREMENT	CHYD
Hazardous waste shipments offered only to licensed transporters	1 1	Z	-	3	4	75.2
Authorization received from TSD facility for wastes shipped off-site X PA manifest used for intrastate shipments Disposer state manifest or EPA format manifest used for out-of-state shipments X Manifests filled out properly and completely Manifests routed properly and within time limits (24 hours) Manifests routed properly and within time limits (24 hours) Manifests routed properly and within time limits (24 hours) Manifests routed properly and within time limits (24 hours) Manifests routed properly and within time limits (24 hours) Manifests routed properly and within time limits (24 hours) (a) Manifests routed properly and within time limits (24 hours) (b) Manifests routed properly and within time limits (24 hours) (c) Manifests routed properly and within time limits (24 hours) (d) Manifests routed properly and within time limits (24 hours) (d) Manifests routed properly and within time limits (24 hours) (d) Manifests routed properly and within time limits (24 hours) (d) Manifests routed properly and within time limits (24 hours) (d) Manifests routed properly and within time limits (24 hours) (d) Manifests routed properly and within time limits (24 hours) (d) Manifests routed properly and visit of time and labeled (24) (d) Manifests routed properly and visit properly marked and labeled (25) (d) Manifests routed proper containers and properly marked and labeled (26) (d) Manifests routed proper containers and properly marked and labeled (26) (d) Manifests routed proper containers and properly marked and labeled (26) (d) Manifests routed proper containers and properly marked and labeled (26) (d) Material propers and accordance with 75.265(g) (e) Manifests routed properly dealing accordance with required (26) (e) Manifests routed properly and within time limits (24 hours) (f) Manifests routed properly dealing accordance with required (26) (g) Manifests routed properly dealing accordance with required (26) (g) Manifests routed properly dealing accordance with 75.26	·	1)		\perp	Identification number	(c) {
X PA manifest used for intrastate shipments X Disposer state manifest or EPA format manifest used for out-of-state shipments X Manifests filled out properly and completely X Manifests routed properly and within time limits (24 hours) X Proper U.S. DOT shipping containers or packages X Shipping containers marked and labeled according to U.S. DOT X Containers of 110 gal. or less marked with required PA label X Placards offered to transporter X Wastes accumulated on-site for less than 90 days X Containers managed in accordance with 75.265(g) X Containers managed in accordance with 75.265(g) X Containers clearly marked with accumulation date and visible for inspection X Records retained at designated location for 20 years X Quarterly reports submitted to the Department X Exception reporting procedures followed X Preparedness, Prevention and Contingency Plan approved and implemented X Preparedness, Prevention and Contingency Plan approved and implemented X Personnel training program 265 X Personnel training program 265 X Personnel training program annual review 265 X Personnel training storage to accurately identify contents Act Ballity operaged to minimize the possibility of fire explosion.	L	X	4	_	Hazardous waste shipments offered only to licensed transporters	(6) (
Disposer state manifest or EPA format manifest used for out-of-state shipments K. Manifests filled out properly and completely K. Manifests routed properly and within time limits (24 hours) K. Proper U.S. DOT shipping containers or packages K. Shipping containers marked and labeled according to U.S. DOT Containers of 110 gal. or less marked with required PA label Flacards offered to transporter K. Wastes accumulated on-site for less than 90 days Wastes stored in proper containers and properly marked and labeled Containers managed in accordance with 75.265(g). Containers clearly marked with accumulation date and visible for inspection K. Records retained at designated location for 20 years (h) Cuarterly reports submitted to the Department (i) Exception reporting procedures followed K. Spill reporting procedures followed K. Preparedness, Prevention and Contingency Plan approved and implemented M. Preparedness, Prevention and Contingency Plan approved and implemented M. Preparedness, Prevention and Contingency Plan approved and implemented M. Personnel training program 265 M. Personnel training program annual review 265 (f) Drums labled during storage to accurately identify cohtents Act [5] Drums labled during storage to accurately identify cohtents Act [6]		X	1		Authorization received from TSD facility for wastes shipped off-site	(b)
X		X		·		(e) (1
Manifests routed properly and within time limits (24 hours) X		X				(e)(1)
X Proper U.S. DOT shipping containers or packages (f X Shipping containers marked and labeled according to U.S. DOT f) X Containers of 110 gal. or less marked with required PA label f) X Placards offered to transporter (f) X Wastes accumulated on-site for less than 90 days (g) X Wastes stored in proper containers and properly marked and labeled (g) X Containers managed in accordance with 75.265(g) (g) X Containers clearly marked with accumulation date and visible for inspection (g) X Records retained at designated location for 20 years (h) X Quarterly reports submitted to the Department (i) X Exception reporting procedures followed (j) X Hazardous waste disposal plan, if required (i) X Spill reporting procedures followed (m) (m) X Preparedness, Prevention and Contingency Plan approved and implemented (m) (g) X Personnel training program 265 (f) X Personnel training program annual review 265 (f) X Drums labled during storage to accurately identify contents Act (h) Calility operated to minimize the possibility of fire explosion (h) Calility operated to minimize the possibility of fire explosion (h) Calility operated to minimize the possibility of fire explosion (h) Calility operated to minimize the possibility of fire explosion (h) Calility operated to minimize the possibility of fire explosion (h) Calility operated to minimize the possibility of fire explosion (h) Calility operated to minimize the possibility of fire explosion (h) Calility operated to minimize the possibility of fire explosion (h) Calility operated to minimize the possibility of fire explosion (h) Calility operated to minimize the possibility of fire explosion (h)	•	χ	1.		Manifests filled out properly and completely	(e) (1
Shipping containers marked and labeled according to U.S. DOT Containers of 110 gal. or less marked with required PA label Placards offered to transporter (f) Wastes accumulated on-site for less than 90 days Wastes stored in proper containers and properly marked and labeled Containers managed in accordance with 75.265(g) Containers clearly marked with accumulation date and visible for inspection Records retained at designated location for 20 years (h) Quarterly reports submitted to the Department Exception reporting procedures followed What Hazardous waste disposal plan, if required X Special requirements followed for international shipments (o) Personnel training program 265 Personnel training program annual review 265 (f) Drums labled during storage to accurately identify contents Act prescription propersion and maining the possibility of fire explosion		X		ŀ	Manifests routed properly and within time limits (24 hours)	(e)(2
Containers of 110 gal. or less marked with required PA label Placards offered to transporter Wastes accumulated on-site for less than 90 days Containers managed in accordance with 75.265(g) Containers managed in accordance with 75.265(g) Containers clearly marked with accumulation date and visible for inspection Records retained at designated location for 20 years (h) Carterly reports submitted to the Department Exception reporting procedures followed X Exception reporting procedures followed X Preparedness, Prevention and Contingency Plan approved and implemented X Personnel training program 265 (f) Drums labled during storage to accurately identify contents Act Pacillity operated to minimize the possibility of fire explorion		Ý			Proper U.S. DOT shipping containers or packages	(£) (1
Placards offered to transporter (f.		χ	ŀ		Shipping containers marked and labeled according to U.S. DOT	f)(1)
Wastes accumulated on-site for less than 90 days X Wastes stored in proper containers and properly marked and labeled (g) X Containers managed in accordance with 75.265(g) X Containers clearly marked with accumulation date and visible for inspection (g) X Records retained at designated location for 20 years (h) X Quarterly reports submitted to the Department (i) X Exception reporting procedures followed (j) X Hazardous waste disposal plan, if required (m) X Spill reporting procedures followed (m) X Preparedness, Prevention and Contingency Plan approved and implemented (m) X Personnel training program 265 (f) X Personnel training program annual review 265 (f) Containers managed in accordance with 75.265(g) (g) (g) (g) (g) (g) (g) (g)		χ			Containers of 110 gal. or less marked with required PA label	(£) (1)
Wastes stored in proper containers and properly marked and labeled Containers managed in accordance with 75.265(g)		χ			Placards offered to transporter	(f) (2
Containers managed in accordance with 75.265(g) Containers clearly marked with accumulation date and visible for inspection Records retained at designated location for 20 years (h) Cuarterly reports submitted to the Department (i) Exception reporting procedures followed (j) Hazardous waste disposal plan, if required (m) Preparedness, Prevention and Contingency Plan approved and implemented (m) Personnel training program 265 Personnel training program annual review 265 (f) Drums labled during storage to accurately identify contents Act For Section 403	1	X		Ŀ	Wastes accumulated on-site for less than 90 days	(g) (1
Containers clearly marked with accumulation date and visible for inspection Records retained at designated location for 20 years (h) Quarterly reports submitted to the Department (i) Exception reporting procedures followed (j) X. Hazardous waste disposal plan, if required (ii) X. Spill reporting procedures followed (m) X. Preparedness, Prevention and Contingency Plan approved and implemented (m) X. Special requirements followed for international shipments (o) X. Personnel training program 265 X. Personnel training program annual review 265 (f) X. Drums labled during storage to accurately identify contents Act (b) Facility operated to minimize the possibility of fire explosion 266	1				Wastes stored in proper containers and properly marked and labeled	(g) (l
X Inspection (g)		X	_		The second secon	(g) (1
Quarterly reports submitted to the Department (i) X Exception reporting procedures followed (j) X Hazardous waste disposal plan, if required (m) X Spill reporting procedures followed (m) X Preparedness, Prevention and Contingency Plan approved and implemented (m) X Special requirements followed for international shipments (o) X Personnel training program 265 (f) X Personnel training program annual review 265 (f) X Drums labled during storage to accurately identify contents Act (b) Facility operated to minimize the possibility of fire explosion 126						(g) (1
Exception reporting procedures followed (j) X. Hazardous waste disposal plan, if required (ii) X. Spill reporting procedures followed (m) (iii) X. Preparedness, Prevention and Contingency Plan approved and implemented (m) (iiii) X. Special requirements followed for international shipments (o) X. Personnel training program 265 X. Personnel training program annual review 265 (f) X. Drums labled during storage to accurately identify contents Act 97 Section 403 (b) (f) (f) (f)	1				Records retained at designated location for 20 years	(h)
X Hazardous waste disposal plan, if required (1) X Spill reporting procedures followed (m)	1)				Quarterly reports submitted to the Department .	(i)
Spill reporting procedures followed (m)	1)	1			Exception reporting procedures followed	(j)
X Spill reporting procedures followed X Preparedness, Prevention and Contingency Plan approved and implemented X Special requirements followed for international shipments (o) X Personnel training program 265 X Personnel training program annual review 265 X Drums labled during storage to accurately identify contents Act 97 Section 403 (b) (c) (c) (m)	J	√.			Hazardous waste disposal plan, if required	(1)
X Preparedness, Prevention and Contingency Plan approved and implemented (m) (X Special requirements followed for international shipments (o) (f)	X				Spill reporting procedures followed	(m) (1
Personnel training program 265 (f) Personnel training program annual review 265 Drums labled during storage to accurately identify contents Act 97 Section 403 (b) Facility operated to minimize the possibility of fire explosion 26		T	1	X	Preparedness, Prevention and Contingency Plan approved and implemented	(m) (5
Personnel training program annual review 265 (f) (Drums labled during storage to accurately identify contents Act (b) Facility operated to minimize the possibility of fire explosion (26)	T	X		1	Special requirements followed for international shipments	(o) :
Personnel training program annual review 265 (f) (Drums labled during storage to accurately identify contents Act (b) Facility operated to minimize the possibility of fire explosion (26)	X	1	1	1	Personnel training program 265	(f)
Drums labled during storage to accurately identify contents Act 97 Section 403 [b] Facility operated to minimize the possibility of fire explosion 26	X	1	1	1		(f)(
\	7	-	+	\dagger	Drums labled during storage to accurately identify contents Act	
or discharge of HW to air, soil, surface water, or ground water the	1	-	+	- - F	acility operated to minimize the possibility of fire explosion	<u>(b)</u> 26
	<u> </u>		1	10	r discharge of HW to air, soil. surface water, or ground water	<u>(ħ</u> .

Section I

Closure Plan, Post-Closure Plan, and Financial Requirements

This section is submitted in accordance with the requirements of Sections (264) (o) and (p).

The closure plan identifies all steps that will be necessary to completely close the facility at the end of its intended operating life.

A post-closure plan is not required because this is not a disposal facility and all wastes will be removed at closure.

Delaware Valley Works will maintain an on-site copy of the approved closure plan and all revisions to the plan until the certification of closure completeness has been submitted and accepted by the PaDER. Delaware Valley Works will notify PaDER at least 180 days prior to the date we expect to begin final closure. There are no current plans for closure in the foreseeable future.

Upon completion of closure, Delaware Valley Works will submit to PaDER a certification by both an Allied and a local independent registered professional engineer that the facility has been closed in accordance with the specifications in the approved closure plan.

I-1 Closure Plan

Closure of the container storage facility is not currently planned. However, should future circumstances or decisions dictate that we discontinue use of this facility, the system and procedures which follow will be employed. Any modifications to the existing facility equipment, structures or procedures related to the management of the facility will be reflected in our updating and revising of the closure plan.

This closure plan has been designed to ensure that the facility will not require further maintenance and controls, minimizes or eliminates threats to human health ad the environment, and avoids escape of hazardous waste, hazardous waste constituents, contaminated rainfall, or waste decomposition products to ground, surface water, or the atmosphere.

Allied Corporation Chemical Sector Industrial Chemicals Division

Closure Plan Outline for Container Storage Facility

EPA Facility I. D. Number:	PAD 990823742
Location:	Delaware Valley Works
Address and Telephone No.:	Route 13
	Marcus Hook, PA 19061
•	(302) 798-0621

General Facility Information

One area of Delaware Valley Works is dedicated to the storage of hazardous waste in containers, an area located in the north east section of the plant property (Location A on Figure I-1).

The facility is of permanent design with curbing. The dimensions are approximately 50' \times 98' (4900 sq. ft.) and the design capacity of the facility is 400 \times 55 gal. drums, equivalent to 22,000 gallons total. The waste types which will be stored at the facility include:

EPA Hazard <u>Waste No.</u>	Description	Physical State
DØØ2	B-Naphthalene Sulfonic Acid Filter Muds	Liquid, solid
FØ01	Waste_Solvents	Liquid
FØØ2	Waste Solvents	Liquid
FØØ3	Waste Solvents	Liquid
DØØ1	Flammable Waste, N.O.S.	Liquid, solid
F005, U056, U213 U003, U004	Waste Solvents	Liquid
DØØ2	Waste Organic Stripper	Liquid, solid
DØØ1	Ammonium Chloride with Hexane	Solid

Schedule of Final Closure (Milestone Chart)

- A. Estimated year of closure: 2031*
- B. Final date waste will be added to storage area: June 15, 2031
- C. Date all preprocessing completed: July 15, 2031
- D. Date that all inventory has been removed for off-site disposal: September 15, 2031
- E. Final date facility decontaminated: November 15, 2031
- F. Final date closure completed: December 15, 2031
- G. Total time to close the facility (Justification if closure is longer than six months): six months
 - * Date of closure is unknown. Dates shown are hypothetical to illustrate administrative requirements.

Phase I - Removal of Inventory

Removal of the containerized hazardous wastes, including pallets, will be accomplished by the established procedure of off-site disposal. The containerized wastes will be labeled and manifested according to DOT and RCRA requirements. Transportation and disposal will be through contractual agreements with EPA approved facilities. All recordkeeping requirements will be met.

Phase II - Decontamination of Facility

Decontamination of the waste storage facility will consist of:

- clean-out of collection sump. Maximum volume of liquid is 376 gallons. Water will be tested for pH and flammability. Non-flammable liquid in the pH range of 6.0 to 9.0 will be discharged to the on-site non-hazardous treatment facility. Non-flammable liquid not in the 6.0 to 9.0 pH range will be neutralized to that range prior to discharge to the treatment facility. Flammable liquid will be containerized and disposed off-site.
- 2. Water wash down of floor areas. The wash water will be collected and checked for pH. Water in the 6.0 to 9.0 pH range will be discharged to the on-site treatment facility. Water not in the 6.0 to 9.0 pH range will be neutralized before discharge to the treatment facility.

Phase III - Decontamination of Surrounding Area

Contamination by wastes of surrounding soil is not considered a likely possibility.

Phase IV - Closure Certification

All signs will be removed as an element of the general facility closure. Inspection logs will be closed as required. Closure certification will be provided by a staff registered professional engineer and an independent registered professional engineer. Due to the simplicity of this storage facility, one inspection by the certifying engineers should be sufficient. The certification will be submitted to PaDER.

Administrative Schedule of Final Closure

Facility: Delaware Valley Works

Expected Year of Closure: 2031*

December 15, 2030

Submit final closure plan to PaDER (180 days prior to receiving last volume of waste.)

June 15, 2031

No wastes accepted after this date.

(Actual last "drum" of waste may have been placed in facility weeks or months prior -- specific to waste generation frequency at plant.)

July 15, 2031

Closure should begin by this date (30 days after last waste received.)

September 15, 2031

All waste must be removed from the site (90 days after last waste received.)

December 15, 2031

Closure must be completed (180 days after last waste received or plan approval, whichever is later.)
Included are decontamination of equipment, the facility structures, and owner and independent engineer approval certification of "plan" completion.
Certification submitted to PaDER.

*Date of closure is unknown. Dates shown are hypothetical.

I-2 Post-Closure Plan

Post-closure care will not be needed for this facility because it is not a disposal facility.

I-3 Notice in Deed and Notice to Local Land Authority

Because the site is only a hazardous waste storage facility and not a disposal facility, notation is not necessary in the deed informing potential purchasers of restrictions associated with a disposal site.

I-4 Closure Cost Estimates

Container Storage Area

Phase I	Removing Inventory	
	Off-site disposal estimate	
	 Disposal cost (400 drums @ \$50/drum) Plant labor (32 hours @ \$18.10/hr.) Transportation (5 trips @ \$2000/trip) 	\$ 20,000 579 10,000
	Subtotal	\$ 30,579
Phase II	Clean-out of Collection Sump	
	 Disposal cost (8 drums @ \$50/drum) Plant labor (8 hours @ \$18.10/hr.) Transportation (8 drums @ \$25/drum) 	\$ 400 145 200
	Subtotal	<u>\$ 745</u>
Phase III	Decontamination of Facility	
	<pre>1. Wash down floor areas - plant labor (8 hrs. @ \$18.20/hr.)</pre>	\$ 145
	Subtotal	<u>\$ 145</u>
Phase IV	Closure Certification	
- · ·	 Estimated cost for registered professional engineer (8 hrs. @ \$100/hr., includes expenses and transportation.) 	\$ 800
	Subtotal	\$ - 800
	Estimate of closure cost for Delaware Valley Works Facility	<u>\$ 32,269</u>

I-5 Financial Test and Corporate Guarantee for Closure

Allied Corporation has established the Financial Test and Corporate Guarantee for closure. Attachment I-l is a copy of the significant sections of Allied Corporation's demonstration of financial responsibility to USEPA Region III and PaDER. The attachment includes a letter from Allied's Chief Financial Officer, an auditor's report confirming the results of the financial test, and the auditor's opinion regarding the financial test.

I-6 Post-Closure Cost Estimate

Since all wastes will be disposed off-site, there will be no post closure activities or costs.

I-7 Financial Assurance Mechanism for Post-Closure

Since all wastes will be disposed off-site, there will be no post closure activities or costs.

I-8 Liability Insurance

I-8a Sudden Insurance

Allied Corporation has obtained liability insurance for sudden and accidental occurrences in the amount of \$1 million per occurrence with an annual aggregate of \$2 million. (See Attachment I-2)

I-8b Non-Sudden Insurance

Because the hazardous waste management facility is used only for storage, no liability insurance is required for non-sudden occurrences.

I-8c Financial Test

Allied Corporation has an insurance policy for sudden and accidental occurrences; therefore, the financial test is not necessary.

I-8d Variance Procedure


Delaware Valley Works does not now request a reduction of liability amounts.

I-8e Adjustment Procedures

If the amounts of liability coverage are increased and/or the non-sudden liability coverage requirements are improved by either USEPA or PaDER, Allied Corporation will comply as prescribed by the regulations.

I-9 State Assumption of Responsibility

Delaware Valley Works will not request State assumption of legal or financial responsibilities.



TKP 180-

TKP181

<u>ф</u>

AREA-A

PPD 176-PPD 174-PPD 177-

PPD 179

RED 150 AGT 153 RFD 151 AGT 154 AREA - B AREA - B PCH 163 PCH 163 PCH 163 PCH 169 PCH 159 PCH 159

C-148

